

2

Docket No. GJE-90
Serial No. 10/089,873

In the Specification

Please replace the paragraph on page 3, lines 24-25:

A preferred fibre-opening machine is a willying machine. Other mechanical machines having essentially the same effect will be known to those in the art.

JASH-RESP\GJE\GJE2\GJE-90-supplAmend.doc\DNB\la

In the Specification

Please replace the paragraph on page 3, lines 24-25:

A preferred fibre-opening machine is a wilying machine. Other mechanical machines having essentially the same effect will be known to those in the art.

In the Specification

1-8 (Cancel).

9 (Currently amended). A method of manufacturing an abrasive material, comprising the steps of:

- (i) spraying a nonwoven synthetic fibre fleece with a binder;
- (ii) spreading the sprayed fleece with abrasive;
- (iii) curing the binder; and then,
- (iv) passing the fleece to a mechanical fibre-opening machine to wholly or substantially separate the fibres from one other.

10 (Cancel).

11 (Currently amended). An abrasive material obtainable by a method comprising the steps of:

- (i) spraying a nonwoven synthetic fibre fleece with a binder;
- (ii) spreading the sprayed fleece with abrasive;
- (iii) curing the binder; and then,
- (iv) passing the fleece to a mechanical fibre-opening machine to wholly or substantially separate the fibres from one another.

12 (Cancel).